

# LIFTING TECHNOLOGY

## FOUR POST LIFT

**CM II 4.50**  
VP 251156



### CM II 4.50 VP 251156

The four post CM II 4.50 lifts vehicles of up to 5.0 t. The extra reinforced plates welded onto the runway guarantee optimum stability. The special runway profile and its reinforced cross beams ensure high flexural resistance.

#### PRODUCT DETAILS/ACCESSORIES

Description/Standard delivery:

- Four post lift with electro-hydraulic drive for above-floor installation
- Low drive-on height
- Lowering device for wheel alignment included in standard delivery, with adjustable lock ladder and pneumatically operated latch
- One runway adjustable (without axle jack)
- 2 pcs drive-on ramps, 2 pcs roll-off protection bars
- Packaging included
- Powder coating:
  - Window Grey, RAL 7040 (Columns)
  - Anthracite Grey, RAL 7016 (Runways, Runway structures, Drive-on ramps, Traverses)

#### TECHNICAL DATA

Load capacity	5.0 t
Lifting height max	1.995 mm
Raising time	approx. 30 s
Lowering time	approx. 30 s
Drive-on height	175 mm
Drive-on height with wheel alignment equipment	225 mm
Runway width	630 mm
Runway length	5.350 mm
Total length	6.770 mm
Inside columns	2.900 mm
Overall width	3.350 mm
Motor power	5,5 kW/50 Hz
Supply voltage	3 x 400 V
Fuse protection	16 A time-delay
Net weight	1.650 kg
Reservoir capacity	10 l
Air pressure	8 bar

#### ACCESSORIES

# LIFTING TECHNOLOGY

## FOUR POST LIFT

**CM II 4.50**  
VP 251156



VZ 971333	Integrated Lighting inside of runways (4 Fluorescent Tubes)	VZ 975026	Sliding Plates (2 pcs.) LxWxH: 1060 x 570 x 50 mm
VZ 990390	Lighting (6 lamps) inside of runways	VZ 975655	Set of compensating plates for turntables - length 450/500 mm (plain sheet; 5.35 m runway)
VZ 985059	Hand pump for manual lowering when lift is set on mechanical locks	VZ 975656	Set of compensating plates for turntables - length 450/500 mm (plain sheet; 5.35 m runway)
VZ 971302	Inground set (drive over capable) consisting of short flaps (4)-without extra charge	VZ 975664	Set of compensating plates for turntables - length 450/500 mm (plain sheet; 5.35 m runway)
VZ 975617	Compressed-air quick coupler installed to runway, drive-on and drive-off side (2 pcs)	VZ 975665	Set of compensating plates for turntables - length 450/500 mm (plain sheet; 5.35 m runway)
VZ 975181	Compressed-Air Servicing Unit with Fastening Angle (0 - 10 bar)	VZ 975657	Compensating Plates, Reinforced (2 pcs), L = 500 mm -EXTRA CHARGE-
VZ 990029	Light Barrier Safety Device to avoid Contact with Ceiling	VZ 975027	Aluminium Covers for Sliding Plates (2 pcs.)
VZ 971331	Exit Flaps enable Vehicles to drive over Lift	VZ 975709	Aluminium Covers for Sliding Plates (4 pcs.)
VZ 971503	Extended Approach Ramps (2 pcs.) L = 1500 mm appr. angle 7° -Extra Charge-	<b>SUPPLEMENTARY CHARGES</b>	
VZ 970112	Wheel-Free Jack 3.5 for Four-Post-Lift 4,0/5,0t	VT 998026	Transportkosten Vier-SäulenHebebühne bis 5000 kg Traglast
VZ 975069	Plastic Chocks (4 pcs.) (47 x 132 x 340 mm)	VM 995747	Montagekosten Vier-SäulenHebebühne mit 5000 kg Traglast
VZ 975074	Hard Rubber Blocks, Plug-in Type (4 pcs.) 120 x 100 x 50 mm	VM 996072	Install. Charges f. Ceiling Light Barrier -T&M Basis
<b>AXLE JACK, PLEASE SEE SEPARATE PRICELIST!</b>		VM 995087	Levelling of Scissors-Lift/ Four Post Lift
<b>ACCESSORIES WHEEL ALIGNMENT FOUR-POST-LIFT 5.0 t</b>		VM 999035	Hydraulic Oil (HLP-D 22) per Litre -NET PRICE
VZ 970027	Sliding Plates (2 pcs.) Long Version LxWxH: 1465 x 570 x 50 mm	VM 999014	Hydraulic Oil, Biodegradable (HLP 32), per litre -NET
		VM 995661	Assembly Material for Four-Post Lift up to 5000 kg lifting cap.