LIFTING TECHNOLOGY
TWO POST INGROUND LIFT

ZS SQUARE II 5.0 P
VP 252216

ZS SQUARE II 5.0 P
VP 252216

The two post inground lift, with runway, lifts cars and vans of up to 5.0 t. The runway lift, with electro-hydraulic SQUARE lifting unit, is optimally suited for the quick lifting of vehicles. Thanks to the already present rails, an axle jack for wheel-free lifting can also be added to the runway for vehicles with a 4300 mm wheelbase. Optional: Conversion to vehicle reception, wheel alignment or inspection lift with axle play detector, as well as various types of installation (flush-mounted runway, with or without floor compensation). The torsion-resistant SQUARE posts guarantee maximum safety and outstanding tensile strength.

PRODUCT DETAILS/ACCESSORIES

Description:
Two-post in-floor lift with driving platforms

Description of driving platform:
- Driving platform length 4800 mm ideal for cars and transporters
- Ample freedom ofmovement below the lifting platform thanks to the compact post-lifting unit and resulting optimum lighting below the raised vehicle
- Optionally, can be upgraded to vehicle check-in lift with axle play tester to inspect chassis assemblies
- Optional conversion to chassis measurement lift with precisely aligned driving platforms, sliding plates for tension-free wheel support, driving platform levelling and axle measurement supports
- A high-quality powder-coated platform covering assists in corrosion protection and adds a significant upgrade in terms of appearance
- Optional driving platform coating with granulate coating
- Pre-integrated compressed air connection and optional 230V/1PH energy supply in runways
- All cables are protected inside the SQUARE post
- Optional, no-dazzle rotatable LED lighting
- Various assembly variants for optimum use:
  - Driving platform resting on floor with low drive-on height and platform movement area with no tripping hazard edges
  - Driving platforms flush with floor to facilitate driving onto the lift, no protruding assemblies in the lift area
  - Driving platforms flush with floor to facilitate driving onto the lift, no protruding assemblies in the lift area with complete floor levelling of the platform movement area with no tripping hazard edges
- Runways and ground levelling pre-equipped for the use of an optional axle lift
- Pinch point and shear point protection thanks to CE stop

SQUARE lift unit:
- Outstanding rigidity and optimum safety thanks to torsion-resistant square post
- Very quiet pump and very quiet electric motor in corrosion-proof oil-submerged design, optionally with bio oil
- Electronic lift control with no-contact, wear-free limit switches and visual errordisplay
- Very smooth running due to special long-life nickel coating on posts that promotes sliding, with robust, low-maintenance post design
- Protected internal hydraulic safety cylinder guarantee lengthy service life
- Mobile synchronisation and safety yoke for careful distribution of force in the post guide as standard
- High lifting/lowering speeds are guaranteed (max. 30/20 s)
- Battery-operated emergency lowering
- Optimisation of workplace ergonomics mentioned thanks to optional, standard-independent control via traffic-light energy module or flush-mounted switching system

Scope of delivery:
- Driving platform 4800 mm, powder-coated Anthracite Grey (RAL 7016)
- Lift unit with hydraulic assembly
- Ramps and drive-on plates
- Rapid-action compressed-air coupling mounted on driving platform
- Wiring and mounting material
- Lift unit with movable yoke
- Installation box/installation frame not included in delivery
- Emergency DOWN cable for connection to switch box
- Control unit with 2 x 10 m control cables (flexible oil cables)
- Lockable master switch
- Operating manual and test log
- EC Declaration of Conformity CE

LIFTING TECHNOLOGY
TWO POST INGROUND LIFT

ZS SQUARE II 5.0 P
VP 252216

TECHNICAL DATA

Load capacity CE	5000 kg
Dimensions of driving	
platform (L x W x H)	4800 x 617 x 150 mm
Inner drive-through width	950 mm
Total dimensions (L x W x H)	5868 x 2184 x 150 mm
Max. lifting height	2050 mm
Post dimensions, square	180 mm
Post spacing	1567 mm
Installation depth	2382 mm
Lifting/lowering time depending on load	approx. 30/20 s
Hydraulic oil volume	
(not included in delivery)	approx. 28 l
Operating pressure	180 bar
Control unit (H x W x D)	320 x 220 x 120 mm
Drive power	3.0 kW
Fuse gG	16 A
Power supply	3/N/PE 400 V 50 Hz

ACCESSORIES

VZ 975013	Runways with Granulate Coating -Extra Charge
VZ 972425	Flush-fitted Runway Install. Drive-over Flaps instead of Drive-on Ramps (4 pcs.)
VZ 972153	Auto chocks (2 pcs.), only for flush-fitted installation of runways
VZ 972424	Roll-off Protection, Hinged (MAHA) only for Runways w. Foundation Install. (2 pcs.)
VZ 972150	Exit ramp, for above-floor installation, length 1000 mm
VZ 990432	LED Illuminant, 2 pcs (1 pcs per each Runway)
VZ 990433	LED Illuminant, 4 pcs (2 pcs per each Runway)
VZ 990012	Shockproof socket 230 V, integrated into runway (only in combination w. lighting)
VZ 990199	Safety Switch for Lift in conjunction with Brake Testers MAHA
VZ 975181	Compressed-Air Servicing Unit with Fastening Angle (0 - 10 bar)
VZ 972268	Floor compensation, pneumatic, f. runway 4.8 m (only in comb. w. Installation Frame 972269)
VZ 972269	Installation frame f.ZS runway 4.8 m flush-fitted, w. floor compensation (perm. formwork)
VP 985007	Axle Play Detector, PMS 3/X for Installation in Front of Scissors Lift
VP 985024	Axle Play Detector, Model: PMS 3/XL with Lowerable Prism Blocks
VZ 995021	Installation Costs for Standard Installation of Play Detector -NET PRICE-
VZ 972107	Levelling legs, adjustable, working height approx. 1200 mm
VZ 972115	Telescopic Levelling Legs for 2 positions (min. 1375 mm, max. 1700 mm)
VZ 975026	Sliding Plates (2 pcs.) LxWxH: 1060 x 570 x 50 mm
VZ 970027	Sliding Plates (2 pcs.) 'Long Version' LxWxH: 1465 x 570 x 50 mm
VZ 975027	Aluminium Covers for Sliding Plates (2 pcs.)
VZ 971316	Sliding Plates Precision (2 pcs.) LxWxH: 1150x600x50 mm
VZ 975032	Compensating plates (2) for equipment without turning plates
VZ 975630	Set of compensating plates for turntables and sliding plates with granulate coating
VZ 972556	Installation tub for lifts 1580 mm cylinder distance MODEL: EW SA 1580

SUPPLEMENTARY CHARGES

VT 998239	Internal transport -SOUTHTwo-/Four-post lift with runways
VT 998240	Internal transport -NORTHTwo-/Four-post lift with runways
VT 998241	Internal transport -SOUTHFoundation frame for runway
VT 998242	Internal transport -NORTHFoundation frame for runway
VT 998237	Internal transport -SOUTHInstallation tub (1 - 4 pcs)
VT 998238	Internal transport -NORTHInstallation tub (1 - 4 pcs)
VM 996155	Montagekostenpauschale für Zweistempel-Hebebühne mit Fahrfläche
VM 996020	Montagekosten Bodenausgleich bei Einbau in Zwei-/Vier Stempel-Fahrflächen-Hebebühne
VM 996213	Montagekosten Einbaurahmen für bodenebene Fahrflächen brücke
VM 999035	Hydraulic Oil (HLP-D 22) per Litre -NET PRICE
VM 999036	Environmental-Friendly Hydr. Oil (PE-B 30), per litre -NET-
VV 997046	Packing Charges Post Inground Lift - within Europe -

VV 995110	Extra Charge for Driving Platforms of Two-	Cylinder Lift -within Europe-