

# LIFTING TECHNOLOGY **AXLE JACK**

**AL II 4.0 PH W** VP 985065





# **AL II 4.0 PH W** VP 985065

The axle jack has proved successful thanks to its robust, tried and tested technology and is suitable for a load capacity of up to 4.0 t. Operation is either via manual hydraulic or hydro-pneumatic system. The axle jack can be supplemented by a wide range of accessories.

#### PRODUCT DETAILS/ACCESSORIES

Powder coating in RAL 7016, anthracite incl. carriage incl. air supply set (spiral hose, guide rope)

incl. 2 120 mm rubber discs incl. 2 adapter sockets for rubber discs incl. 3 lift extenders measuring 50 / 100 / 200 mm

### **TECHNICAL DATA**

Load capacity	4000 kg at 8.5 bar
Min. / max. operating pressure	8.5 bar / 12 bar
Minimum air quantity	500 l/min
Stroke (effective stroke)	250 mm
Extension length	796 - 1650 mm

## **ACCESSORIES**

rollers	rollers	SUPPLEMENTARY CHARGES	
		VT 998045 Transportkosten Achslift	
	Axle lift guide rollers for pit profiles with tapered rollers	VM 996144 Montage Achslift	

SLiFT - a brand of MAHA / Hoyen 20 / 87490 Haldenwang / Germany Phone: +49 8374 585 0 / Fax: +49 8374 585 0 / sales@maha.de / www.slift.de



