## LIFTING TECHNOLOGY ONE POST INGROUND LIFT

### **ES SOLIST 3.0 X** VP 252324





### **ES SOLIST 3.0 X** VP 252324

One-post inground lift with swing arm X-supports, to pick up vehicles in the sill area. Suitable for cars, pick-up points underneath the vehicle.

#### **PRODUCT DETAILS/ACCESSORIES**

Description:

One-post inground lift with swing arm X-supports, to pick up vehicles in the sill area. Suitable for cars, pick-up points underneath the vehicle

Swing arm support (X):

- Optimum vehicle pick-up with maximum accessibility, especially for repairs from outside in the sill or engine area
- Double telescopic swing arm support for stepless adjustment
- Swing arm extensions with min. height of 104 mm
- Precise pick-up of vehicles due to height-adjustable support discs with thread and plug-in system
- Multiflexible plug-in system for support extenders or special supports for various vehicle types for secure, positive-locking vehicle fixation in the product range
- Comes standard with fully rubberised support plate without metal parts to exclude electrical conductivity
- · Automatically engaging support arm lock

#### SOLIST lift unit:

- Corrosion-proof hydraulic piston, self-lubricating since it dips into hydraulic oil with each stroke
- Low-noise operation due to very quiet motor in the installation box

- · Optionally usable with mineral organic oil with high durability
- · Electronic lift control with visual error display
- Hydraulic power unit inside installation box (standard), can optionally be positioned outside
- Simple, suspended installation of the lift, ensuring advantageous force transmission into the hall floor
- High lifting/lowering speeds are guaranteed in a loaddependent range of 30 35 seconds
- Integrated, battery-operated emergency lowering
- Optimum workplace ergonomics thanks to optional, standardindependent control system via energy box or flush-mounted switching system

#### Scope of delivery:

- Swing arm support (X) with swing arm carrier, anthracite grey (RAL 7016), and galvanised swing arm extensions
- Medium pressure lifting unit with clamping system
- · Cable and fastening material
- Installation box/frame not included in scope of delivery
- · Emergency-down cable for connection to the control box
- Control unit with 10 m control cable (oil flex cable)
- · Lockable main switch
- Pinch point protection by CE-stop instead of foot deflector
- Operating instructions
- EC/UKCA Declaration of Conformity

#### **TECHNICAL DATA**

Load capacity CE	3000 kg
Adjustment range of support discs	84 - 105 mm
Installation height	104 mm
Lifting height max.	1968 mm
Lifting/lowering time, load-dependent	approx. 35/35 s
Hydraulic oil quantity (not incl. in delivery) approx. 50 l	
Oil quality	HLP-D 22
Operating pressure	32 bar
Recommended installation box	VZ 972554

Technical Datasheet / 17/11/2023

# LIFTING TECHNOLOGY ONE POST INGROUND LIFT





#### **TECHNICAL DATA**

Control unit (H x W x D)	320 x 220 x 120 mm
Drive power	3.0 kW
Fuse protection gG	16 A
Power supply	3/N/PE 400 V 50 Hz

۲

#### ACCESSORIES

VZ 972554	Installation tub for lifts for one-post inground lifts VZ 975	VZ 975601	Support arbor (2 pcs.) for MB Sprinter/VW Crafter
ACCESSORI	MODEL: EW SA 0 ES FOR SWING ARMS	VZ 971227	Special Prism Support for MB G-Class w/o Tread Plate Plug-In System - (4 pcs.)
VZ 971539	Storage Tray MAHA stainless steel, magnetic for small parts, (2 pcs)	VZ 971520	Special Prism Support for MB G-Class with Tread Plate Plug-In System - (4 pcs.)
VZ 971635	Rubberised foil for tools on the swing arms (4 pcs) Dimensions: 185 x 83 mm	VZ 975602	Grate 4015 x 2000 mm ES-Lift, 1000 kg Wheel Load incl. Installation Frame
VZ 971220	Support Plate Extension 50 mm, galvanized, (2	SUPPLEME	NTARY CHARGES
VZ 971221	pcs.) Diameter of supports 35 mm Support Plate Extension 100 mm galvanized (2	VT 998235	Transport Werkverkehr -SÜDEin-/Zwei-Stempel- Hebebühne mit Tragwerk
		VT 998236	Transport Werkverkehr -NORDEin-/Zwei-Stempel-
VZ 971222	Support Plate Extension 150 mm galvanized (2		Hebebühne mit Tragwerk
VZ 071000		VT 998237	Transport Werkverkehr -SÜDEinbauwanne (1 - 4 Stück)
VZ 971223	VZ 971223 Support Plate Extension 200 mm galvanized (2 pcs.) Diameter of supports 35 mm	VT 998238	Transport Werkverkehr -NORDEinbauwanne (1 - 4
VZ 971224	Holding Device for 2 Support Plate Extensions,	VT 990200	Stück)
can be mount	can be mounted to Wall (2 pcs.)	VT 998211	Transport Werkverkehr -SÜDGitterberostung
	Non-skid device for vehicles with longitudinal	VT 998212	Transport Werkverkehr -NORDGitterberostung
VZ 971247		VM 996007	Montagekosten EinstempelHebebühne inkl.
	mm plug-in system- (4 pcs.)	V/N 4 0000005	Tragwerk/Arme
VZ 071640		VM 999035	Hydraulic Oil (HLP-D 22) per Litre -NET PRICE
	Strap attachment on support arm thread for tilt protection	VM 999036	Environmental-Friendly Hydr. Oil (PE-B 30), per litre -NET-
VZ 971226	Special Prism Support for MB Sprinter and VW Crafter Plug-In System - (2 pcs.)	VV 997046	Packing Charges Post Inground Lift within Europe

SLiFT - a brand of MAHA / Hoyen 20 / 87490 Haldenwang / Germany Phone: +49 8374 585 0 / Fax: +49 8374 585 0 / sales@maha.de / www.slift.de

۲