

# LIFTING TECHNOLOGY

## TWO POST INGROUND LIFT

**ZS DUETT 3.5 FT**  
VP 252319



### ZS DUETT 3.5 FT

#### VP 252319

Two-post inground lift with flat head supports, to pick up vehicles in the sill area. Suitable for cars, pick-up points underneath the vehicle.

#### PRODUCT DETAILS/ACCESSORIES

##### Description:

Two-post inground lift with flat head supports, to pick up vehicles in the sill area.  
Suitable for cars, pick-up points underneath the vehicle

##### Flat head support (FT H):

- Flat head extensions adaptable for different vehicle types, telescopic from 1400 - 2000 mm in standard
- Flexible, optional range of support plates in 'longer - wider - flatter' versions ensures perfect accommodation of all current and future vehicle models
- Large pick-up areas due to exchangeable support plate system cover the entire vehicle spectrum
- Easier, tyre-preserving drive-on thanks to all-round bevelled extensions combined with low construction height and rubber support plate (height no more than approx. 60 mm)
- Rubber support plate enables time-saving direct pick-up
- Optional flush-floor installation for easier passing over lift

##### DUETT lift unit:

- Lift with precise mechanical toothed rack synchronisation and simultaneous redundant mechanical safety feature
- Corrosion-proof hydraulic piston, self-lubricating since it dips into hydraulic oil with each stroke
- Low-noise operation due to very quiet motor in the installation

##### box

- Optionally usable with mineral organic oil with high durability
- Electronic lift control with visual error display
- Hydraulic power unit inside installation box (standard), can optionally be positioned outside
- Simple, suspended installation of the lift, ensuring advantageous force transmission into the hall floor
- High lifting/lowering speeds are guaranteed in a load-dependent range of 30 - 35 seconds
- Integrated, battery-operated emergency lowering
- Optimum workplace ergonomics thanks to optional, standard-independent control system via energy box or flush-mounted switching system

##### Scope of delivery:

- Flat head supports, hot-dip galvanised
- Medium-pressure lift unit with clamping system
- Wiring and mounting material
- Installation box/installation frame not included in delivery
- Emergency lowering cable for connection to switch box
- Control unit with 2 x 10 m control cable (oil flex cable)
- Lockable main switch
- Pinch point protection by CE stop instead of foot guard
- Operating instructions
- CE/UKCA Declaration of conformity

#### TECHNICAL DATA

Load capacity CE	3500 kg
Post distance	1350 mm
Longitudinal support extendable in notch steps	.
	1400 - 2000 mm
Transverse support by repositioning	880 - 1820 mm
Size of support plate (L x B)	355 x 400 mm
Lifting height max.	1960 mm
Installation depth	2300 mm
Post diameter	90 mm

# LIFTING TECHNOLOGY

## TWO POST INGROUND LIFT

**ZS DUETT 3.5 FT**  
VP 252319



### TECHNICAL DATA

Toothed rack diameter, stainless steel	40 mm
Lifting/lowering time, load-dependent	approx. 35/35 s
Hydraulic oil quantity (not incl. in delivery) approx. 50 l	
Oil quality	HLP-D 22
Operating pressure	39 bar
Recommended installation box	VZ 972555
Control unit (H x W x D)	320 x 220 x 120 mm
Drive power	3.0 kW
Fuse protection gG	16 A
Power supply	3/N/PE 400 V 50 Hz

### ACCESSORIES

- VZ 972613 Reinforcement ZS DUETT 3.5 FT with post diameter 125 mm -EXTRA CHARGE-
- VZ 972555 Installation tub for lifts 1350 mm cylinder distance MODEL: EW SA 1350

#### ACCESSORIES FOR FLAT LIFTING HEADS

- VZ 972452 Flat lifting heads with extended support range 100 mm (1 set - 2 pcs) -EXTRA CHARGE-
- VZ 972453 Flat lifting heads w. extra wide supports Model: R5G 3.5 -EXTRA CHARGE-
- VZ 972423 Flat lifting heads with Granulate Coating instead of Rubber Support -EXTRA CHARGE-
- VZ 975927 Rubber Chocks Set pyramidal h=40 mm, 120x120 mm (4 pcs.) MODEL: GK 12/4 set
- VZ 975634 Rubber Chocks Set pyramidal h=80 mm, 120x120 mm (4 pcs.) MODEL: GK 12/8 set
- VZ 975069 Plastic Chocks (4 pcs.) (47 x 132 x 340 mm)
- VZ 975586 Rubber pads flat 100 x 150 x 20 mm (4 pieces)

#### FLUSH-FITTED INSTALLATION

- VZ 972519 ZS Flat lifting head for flush-fitted installation
- VZ 972420 Inst. Frame f. Flush Mounted 2 Post Inground Pad Type Lift Model: D-ER

### SUPPLEMENTARY CHARGES

- VT 998235 Transport Werkverkehr -SÜDEin-/Zwei-Stempel-Hebebühne mit Tragwerk
- VT 998236 Transport Werkverkehr -NORDEin-/Zwei-Stempel-Hebebühne mit Tragwerk
- VT 998237 Transport Werkverkehr -SÜDEinbauwanne (1 - 4 Stück)
- VT 998238 Transport Werkverkehr -NORDEinbauwanne (1 - 4 Stück)
- VT 998231 Transport Werkverkehr -SÜDEinfassungsrahmen
- VT 998232 Transport Werkverkehr -NORDEinfassungsrahmen
- VM 996001 Montagekosten ZweistempelHebebühne inkl. Tragwerk/Arme
- VM 996007 Montagekosten EinstempelHebebühne inkl. Tragwerk/Arme
- VM 996211 Montagekosten Einfassungsrahmen für bodenebene Flachträgerbrücke
- VM 999035 Hydraulic Oil (HLP-D 22) per Litre -NET PRICE
- VM 999036 Environmental-Friendly Hydr. Oil (PE-B 30), per litre -NET-
- VV 997046 Packing Charges Post Inground Lift within Europe