

LIFTING TECHNOLOGY

TWO POST INGROUND LIFT

ZS SQUARE II 6.5 KS
VP 252322



ZS SQUARE II 6.5 KS

VP 252322

Two-post inground lift with swing arms, to pick up vehicles in the sill area or at the frame. Suitable for small vehicles up to vans (up to 6.5t) with long wheelbase.

PRODUCT DETAILS/ACCESSORIES

Description:

Two-post inground lift with swing arms, to pick up vehicles in the sill area or at the frame. Suitable for small vehicles up to vans (up to 6.5t) with long wheelbase

Swing arm support (6.5 KS):

- Optimum vehicle pick-up with maximum accessibility, especially for repairs under the vehicle
- Triple telescopic swing arm support for stepless adjustment for a large and flexible pick-up range
- Large clearance for easy approach to the lift with bevelled edges on the swing arm carrier to protect the rims
- Precise pick-up of vehicles due to height-adjustable support discs with thread and plug-in system
- Multiflexible plug-in system for support extenders or special supports for various vehicle types for secure, positive-locking vehicle fixation in the product range
- Comes standard with fully rubberised support plate without metal parts to exclude electrical conductivity
- Automatically engaging support arm lock, which is convenient and ergonomic to operate and particularly suitable for manual readjustment of the support arms
- Tool tray on swing arm carrier included in standard scope of delivery

SQUARE lift unit:

- Outstanding rigidity and optimum safety thanks to torsion-resistant square posts
- Low-noise operation due to very quiet motor in the installation

box

- Optionally usable with mineral organic oil with high durability
- Electronic lift control with no-contact, wear-free limit switches and visual error display
- Very smooth running due to sliding, long-life special nickel coating on posts with robust, low-maintenance post guide
- Protected internal hydraulic safety cylinder guarantees lengthy service life
- Movable synchronisation and safety yoke for redundant operation (acc. to EN DIN 1493)
- High lifting/lowering speeds are guaranteed in a load-dependent range of 20-30 seconds
- Integrated, battery-operated emergency lowering
- Optimum workplace ergonomics thanks to optional, standard-independent control system via energy box or flush-mounted switching system

Scope of delivery:

- Swing arm support (KS) with swing arm carrier and swing arm extensions, anthracite grey (RAL 7016)
- Magnetic wheel nut tray (2 pcs)
- Lifting unit with clamping system and movable yoke
- Cable and fastening material
- Installation box/frame not included in scope of delivery
- Emergency-down cable for connection to the control box
- Control unit with 10 m control cable (oil flex cable)
- Lockable main switch
- Pinch point protection by CE stop instead of foot deflector
- Operating instructions
- EC/UKCA Declaration of Conformity

TECHNICAL DATA

| | |
|-----------------------------------|------------------|
| Load capacity CE | 6500 kg |
| Post distance | 2700 mm |
| Drive-through width | 2440 mm |
| Overall width | 3380 mm |
| Min. height of support arms | 109, 124, 144 mm |
| Adjustment range of support discs | 101 - 137 mm |

LIFTING TECHNOLOGY

TWO POST INGROUND LIFT

ZS SQUARE II 6.5 KS
VP 252322



TECHNICAL DATA

| | |
|---|--------------------|
| Lifting height max. | 1952 mm |
| Installation depth | 2382 mm |
| Post dimensions, square | 180 mm |
| Lifting/lowering time, load-dependent | approx. 40/35 s |
| Hydraulic oil quantity (not incl. in delivery) approx. 28 l | |
| Oil quality | HLP-D 22 |
| Operating pressure | 215 bar |
| Recommended installation box | VZ 972559 |
| Control unit (H x W x D) | 320 x 220 x 120 mm |
| Drive power | 3.0 kW |
| Fuse protection gG | 16 A |
| Power supply | 3/N/PE 400 V 50 Hz |

ACCESSORIES

VZ 972559 Installation tub for lifts 2700 mm cylinder distance MODEL: EW SA 2700

ACCESSORIES FOR SWING ARMS

VZ 971539 Storage Tray MAHA stainless steel, magnetic for small parts, (2 pcs)

VZ 971635 Rubberised foil for tools on the swing arms (4 pcs) Dimensions: 185 x 83 mm

VZ 971220 Support Plate Extension 50 mm, galvanized, (2 pcs.) Diameter of supports 35 mm

VZ 971221 Support Plate Extension 100 mm galvanized (2 pcs.) Diameter of supports 35 mm

VZ 971222 Support Plate Extension 150 mm galvanized (2 pcs.) Diameter of supports 35 mm

VZ 971223 Support Plate Extension 200 mm galvanized (2 pcs.) Diameter of supports 35 mm

VZ 971573 Support Disk Extension 300 mm galvanized (2 pcs.) Diameter of supports 35 mm

VZ 971224 Holding Device for 2 Support Plate Extensions, can be mounted to Wall (2 pcs.)

VZ 975050 Non-skid device for vehicles with longitudinal frame up to 100 mm width (2 pcs)

VZ 971247 Support Plates for VOLVO external diameter 100 mm plug-in system- (4 pcs.)

VZ 971649 Strap attachment on support arm thread for tilt protection

VZ 971226 Special Prism Support for MB Sprinter and VW Crafter Plug-In System - (2 pcs.)

VZ 975601 Support arbor (2 pcs.) for MB Sprinter/VW Crafter

VZ 971227 Special Prism Support for MB G-Class w/o Tread Plate Plug-In System - (4 pcs.)

VZ 971520 Special Prism Support for MB G-Class with Tread Plate Plug-In System - (4 pcs.)

SUPPLEMENTARY CHARGES

VT 998235 Transport Werkverkehr -SÜDEin-/Zwei-Stempel-Hebebühne mit Tragwerk

VT 998236 Transport Werkverkehr -NORDEin-/Zwei-Stempel-Hebebühne mit Tragwerk

VT 998237 Transport Werkverkehr -SÜDEinbauwanne (1 - 4 Stück)

VT 998238 Transport Werkverkehr -NORDEinbauwanne (1 - 4 Stück)

VM 996001 Montagekosten ZweistempelHebebühne inkl. Tragwerk/Arme

VM 999035 Hydraulic Oil (HLP-D 22) per Litre -NET PRICE

VM 999036 Environmental-Friendly Hydr. Oil (PE-B 30), per litre -NET-

VV 997046 Packing Charges Post Inground Lift within Europe